

## HARDWARE FEATURES

- Stainless steel envelope
- Counter-weighted vertical sliding door
- In-line strainer
- LED Lighted chamber
- Multiple fixtures available
- Casters for easy installation

### RESULTING IN...

- + Superior support removal
- + Evenly treated parts
- + Cycle time reduction

## SOFTWARE FEATURES

- Patent-pending AUTOMAT3D™ platform
- Proprietary *Agitation Algorithms*
- Variable temperature (85-160°F, 29-71°C)
- Intelligent cycle times
- Customizable settings
- One-touch repeatability with recipes storage
- Preventative maintenance schedules

### RESULTING IN...

- + Minimized part breakage
- + Minimal operator intervention
- + Preservation of fine-feature details



## PRODUCT SPECIFICATIONS

### SIZE AND WEIGHT

- Envelope: 40" L x 27.5" W x 26" H  
(102 cm x 70 cm x 66 cm)
- Machine Footprint (Closed door):  
– 68.7" L x 40.7" W x 93.2" H  
(174 cm x 103 cm x 237 cm)
- Machine Footprint (Open door):  
– 129" L x 82" W x 97" H  
(328 cm x 208 cm x 246 cm)
- Approx. Weight: 1500 lbs. (680 kg) empty  
2000 lbs. (907 kg) full

### ELECTRICAL

#### US:

- Voltage: 208V 3 Phase
- Amperage: 50A
- Connector: HBL560C9W


#### EU:

- Voltage: 400V 3 Phase
- Amperage: 25A
- Connector: HBL532P6W

### CONSUMABLES

- Detergent: PLM-201-SPRAY for FDM

### SAFETY FEATURES

- Emergency stop
- Auto-interrupt
- Compliant with all OSHA regulations
- 

### MATERIALS AND TECHNOLOGIES



#### POSTPROCESS TECHNOLOGIES INC.

2495 Main Street, Suite 615, Buffalo NY 14214 USA  
info@postprocess.com +1.866.430.5354

#### POSTPROCESS TECHNOLOGIES INTERNATIONAL

49 Impasse du Hameau, 06250 Mougins, France  
+33 (0)4 22 32 68 13